



MATERIAL / MANUFACTURING METHOD

MATERIAL

Crown: 6-4 Titanium Grades

Sole: 3-1-1-1 Titanium

Face: Super438FG-X

Neck: Light density fullerene titanium

PREPARATION

Crown Sole: superplastic forming + diaphragm forming method

Face: Superplastic forming + high-precision hot rod forging

Neck: High quality casting method

FINISH & COLOR

Finish: Mirror Finish + Double Gold IP

Coating: Luster Red + Red Brown Gradation

CLUB	1W			
LOFT (°)	9.5	10.5	11.5	12.5
LIE ANGLE (°)	60	60	60	60
PROGRESSION (mm)	15.5	16.4	17.8	19.0
HEAD VOLUME (cm ³)	460	460	460	460
LENGTH (INCH)	47	47	47	47
GROSS WEIGHT (G) / BALANCE	S	260 / D4	260 / D4	-
	SR	258 / D3	258 / D3	258 / D3
	R	255 / D2	255 / D2	255 / D2
	R2	-	252 / D1	252 / D1

"-" is a spec for custom order.

Normal order line length range: 45.5 to 47.5 inches.

The length 47.5 inches of this product is equivalent to 48 inches of the limit length by R & A rule "60 degree method".

SHAFT



NAME	MAJESTY LV730			
FLEX	S	SR	R	R2
WEIGHT (G)	41	39	38	37
TORQUE	5.0	5.0	5.0	5.1
KICK POINT	Low			
MATERIAL	Ultra-low resin Ultra-thin carbon + Ultra-high elasticity 78 t Ultra-thin carbon + "Pyrophile®" MR70			



GRIP

NAME	MJ Light 4 25D
WEIGHT (G)	25
INNER DIAMETER	D
ADD COLOR	Gold